

# SEKONIC

Optical Mark Reader

# SR-450

SPEED & ACCURACY

COMPACT DESIGN

*The SEKONIC website  
provides information on all of our latest OMRs.*

*<https://www.sekonic.co.jp/english>*



# SR-450

## Compact & High Speed Model

- Compact enough to be located on your desk top
- High Speed and Accuracy to support efficient operation



## SR-450 Features

### Short-time operation

1. Can read approx. 150 forms/min\*1
2. Can set maximum 200 forms on the hopper

### Accurate reading

1. Can distinguish erasure by density detection
2. Can detect errors during reading\*2

### Compact design

1. Can be located on your desktop
2. Can support private work

### Inherited compatibility

1. Can secure compatibility with SR-430, SR-410 and SR-307
2. Can run with your conventional software

## Usage example

<b>Educational field</b>	School term examination, Quiz in daily class, Student survey, Teacher and lesson evaluation, Course registration, Attendance check, etc.
<b>Business field</b>	Order management, Personnel evaluation, Quality control check, Voting count etc.
<b>Governmental field</b>	National license examinations, etc.
<b>Medical field</b>	Medical questionnaire, Healthcare check, Patient billing, etc.

## Specifications

<b>Read-head</b>	Type of sensor	Photo reflective sensor Single	<b>Form input</b>	Hopper (ADF)	Max. 200 forms Max.
	Reading side	side Standard: Infrared ray (940nm)	<b>Form output</b>	Stacker	200 forms LED (4 pcs)
	Light source	Option: Visible red ray (660nm)	<b>Equipment control</b>	Display	2 pcs (FEED and CLEAR)
		Infrared ray: Pencil only		Operation button	
<b>Scanning</b>	Mark implement	Visible red ray: Pencil and Pen	<b>Connection with PC (Interface)</b>	USB2.0	
	Mark discrimination	16 levels	<b>Compatibility</b>	RS-232C (25 pin / 2,400 to 128,000 bps)	
	Channels	15 channels (0.25 inch)	<b>Electrical requirement</b>	Voltage/Frequency	AC115V/60Hz or AC230V/50 - 60Hz
	Form width	82.55 to 110mm	<b>Operating environment</b>	Temperature/humidity	5 to 35 °C / 40 to 80 %
	Form length	150 to 304.8mm	<b>Acoustical noise</b>	Running	Under 60db
	Number of rows	140 rows	<b>Dimensions</b>	W×H×D	222×171×360mm(Closed)/695×377×171mm(Open)
	Number of columns	15 columns	<b>Device weight</b>	Approx. 6kg	
	Kind of paper	OCR paper and wood free paper	<b>Accessories</b>	Operating manual, Power supply cable, CD-ROM(USB driver, Sample program)*3	
	Paper weight (Thickness)	105 to 157 gsm			
	Feeding speed	Approx. 256 forms/min (maximum)			
	Operation speed	Approx. 150 forms/min*1			

\*1 Throughput speed may vary depending on application software and PC specification. \*2 No mark, Multiple mark, Jam, Double paper feed, etc. / Depending on application software \*3 Supporting OS: Microsoft Windows® 8, 8.1, and 10 Windows® and its logo are trademarks or registered trademarks of Microsoft corporation in the United States and other countries

## SEKONIC CORPORATION

7-24-14, Oizumi-Gakuen-cho, Nerima-ku, Tokyo, 178-8686 Japan

TEL +81-3-3978-2375 FAX +81-3-3922-2144

<https://www.sekonic.co.jp/english>

## OMR Solutions

H.O.: 503, DLF Prime Towers, Okhla Phase-1, New Delhi-110020  
0562-3550410, F 011-47619865

M.: +91 9319123429 +91 8954800532

**SAFETY NOTE** Read the operating manual thoroughly before attempting to use the product.

• Features and specifications are subject to change without notice.  
• Details and colors of the image might be different from ones of the real product.

ISO 9001/ ISO 14001

K19Y1010