

FUJITSU Image Scanner fi-6670

High speed 90 ppm/180 ipm
capable scanner



■fi-6670 Features

■Speedy
The 90 ppm/180 ipm* capable (A4, landscape, 200 dpi) fi-6670 is among the fastest scanners in their class. Their ability to continuously scan 200 sheet mixed batch documents containing paper of different weights, quality and sizes enables both of these scanners to efficiently digitize large volumes of documents. On top of this, the fi-6670 is able to scan paper that is up to 3 m long, which enables them to digitize electrocardiograms, instrumental data readings and other long documents.

* Scanning speeds may vary due to the system environment used.
•System requirements (recommended)
CPU: Intel® Core™ i5 2.5GHz or higher, Memory: 4GB or higher, HDD: 7,200rpm, Interface: USB 3.0/2.0

■Loaded with "intelligent" functions for efficient operation
The fi-6670 is loaded with 2 high end fi Series functions that enable it to efficiently scan mixed batch documents containing paper of different weights, quality and sizes.

- Intelligent multifeed function
The intelligent multifeed function simplifies pre-scanning preparation and improves efficiency by ignoring documents that tend to trigger false multifeed alerts, such as photo and sticky note attached documents.
- Trapezoid-shaped and tab attached document cropping / punch hole removal functionality
In addition to being loaded with a function that ensures that trapezoid-shaped documents as well as index tab and sticky note attached documents are scanned in their entirety, the fi-6670 supports a function that removes the circular and angular punch hole representations that are created from scanning loose-leaf sheets, courier service forms and other similar documents.

■Renewed scanner driver and image capturing software
● PaperStream IP – produce high quality image processing
● PaperStream IP is the scanner driver for fi Series which is based on TWAIN/ISIS standard. With the advanced black and white process, various documents can be automatically and easily converted into image data suitable for OCR (Optical character recognition). High quality image data can be created without pre-setting the scanning settings beforehand.

•PaperStream Capture – enhance batch scanning
PaperStream Capture is an application to scan and manage the scanned data using fi Series scanners. Whether it is adjusting the scanning settings or performing batch scanning, you can complete the tasks easily with the user-friendly UI. With the seamless linkage with PaperStream IP, you can perform high quality image processing and batch scanning at the same time.

■Centralized management of multiple scanners
The bundled "Scanner Central Admin" application allows you to manage multiple scanners together. For example, you can update the scanner settings and drivers, as well as monitor the operating status of each scanner.

■Easy placement
Closable operating panels located on the left and right side of the unit permit the scanner to be placed against a wall or in a corner without affecting operability.



■Post imprinter support (Option)
The fi-6670 supports an imprinter option (fi-667PR) that is capable of printing dates and other information on the back of scanned documents in order to simplify the management of the original document at a later date.



Description		fi-6670
Supported operating systems		Windows® 10 (32-bit/64-bit), Windows® 8.1/8 (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows Vista® (32-bit/64-bit), Windows Server® 2016 (64-bit), Windows Server® 2012 R2 (64-bit), Windows Server® 2012 (64-bit), Windows Server® 2008 R2 (64-bit), Windows Server® 2008 (32-bit/64-bit)
Scanner type		ADF (Automatic Document Feeder)
Scanning modes		Simplex / Duplex, Color / Grayscale / Monochrome
Image sensor type		Color CCD (Charge-coupled device) x 2 (front x 1, back x 1)
Light source		White cold cathode discharge lamp x 4 (front x 2, back x 2)
Multifeed detection		Ultrasonic multifeed defection sensor
Document size	Maximum	A3 Portrait (297 x 420 mm or 11.7 x 16.5 in.), Double letter (279.4 x 431.8 mm or 11 x 17 in.)
	Minimum	A8 Portrait (52 x 74 mm or 2 x 3 in.)
Paper weight (Thickness)	Long page scanning (Maximum)*1	3,048 mm (120 in.)
	Paper Plastic card	A4/Letter size or smaller: 0.04 to 0.25 mm (31 to 209 g/m2, or 8.3 to 56 lb) Over A4/Letter size: 0.06 to 0.25 mm (52 to 209 g/m2, or 14 to 56 lb)
	Color*4	A8 size: 0.152 to 0.25 mm (127 to 209 g/m2, or 34 to 56 lb)
Scanning speed (A4 Landscape)*3		Up to 0.76 mm*2
	Grayscale*4	Simplex: 90 ppm (200 dpi), Duplex: 180 ipm (200 dpi)
	Monochrome*5	Simplex: 80 ppm (300 dpi), Duplex: 160 ipm (300 dpi)
Scanning speed (A4 Portrait)*3	Color*4	Simplex: 70 ppm (200 dpi), Duplex: 140 ipm (200 dpi)
	Grayscale*4	200 sheets (A4: 80 g/m2 or 20 lb) (Active loadable ADF)
	Monochrome*5	White / Black (Selectable)
Paper chute capacity (A4 Landscape)*6		600 dpi
Background colors		
Optical resolution		
Output resolution*7	Color (24-bit)	50 to 600 dpi (adjustable by 1 dpi increments), 1,200 dpi (driver) *8
	Grayscale (8-bit)	
	Monochrome (1-bit)	
Output format		Color: 24-bit
Internal video processing		Grayscale: 8-bit
Interface*9*10		Monochrome: 1-bit
Connector shape		1,024 levels (10-bit)
SCSI terminator		Ultra SCSI, USB 2.0/USB 1.1 (Selectable)
		Ultra SCSI: Shield type 50 pin (pin type), USB: Type B
		Built-in
Image processing functions		Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, De-Screen,Emphasis, Halftone, Dropout color (None /Red /Green /Blue /White /Saturation /Custom), sRGB output, Hole punch removal, Index tab cropping, Split image, De-Skew, Edge correction, Vertical streaks reduction, Cropping, Dither, Static threshold
Power requirements		AC 100 to 240 V ±10%
Power consumption		Operating: 130 W or less Sleep mode: 3.0 W or less Auto Standby (OFF) mode: 0.5 W or less
Operating environment		Temperature: 5 to 35 °C (41 to 95 °F) Relative humidity: 20 to 80 % (Non-condensing)
Dimensions: Width x Depth x Height*11		641 x 432 x 300 mm (25.2 x 17.0 x 11.8 in.) Installation space: 1,179 x 686 x 390 mm (46.4 x 27.0 x 15.4 in.)
Weight		17 kg (37.5 lb)
Included software / drivers		PaperStream IP driver (TWAIN/TWAIN x64/ISIS), 2D Barcode for PaperStream*12, Software Operation Panel, Error Recovery Guide, PaperStream Capture, ScanSnap Manager for fi Series*12, Scan to Microsoft SharePoint*12, ABBYY FineReader for ScanSnap™*12, Scanner Central Admin Agent
Environmental compliance		ENERGY STAR® and RoHS
Included items		ADF paper chute, Stacker, AC cable, USB cable, Setup DVD-ROM,

*1 Capable of scanning documents that exceed A3 size. Documents that exceed 431.8 mm (17 in.) are limited to 400 dpi for lengths up to 863 mm (34 in.). Documents between 863 mm and 3,048 mm (120 in.) in length are limited to 200 dpi.
*2 The fi-6670 supports ISO/IEC card but cannot scan embossed cards.
*3 Actual scanning speeds are affected by data transmission and software processing times.
*4 Indicated speeds are from using JPEG compression.
*5 Indicated speeds are from using TIFF CCITT Group 4 compression.
*6 Maximum capacity varies, depending upon paper weight.
*7 Selectable maximum density may vary depending on the length of scanned document.
*8 When scanning at high resolution (over 600 dpi), some limitations apply to the size of the document that could be scanned, depending on system environment.
*9 You cannot use both SCSI and USB2.0/1.1 interfaces at the same time.
*10 You cannot connect multiple computers to the scanner using each type of interface cables at the same time.
*11 Excluding the ADF paper chute and stacker.
*12 The software can be downloaded from the website designated in the Setup DVD-ROM.

■ Options

Description	Parts number	Comments
Post Imprinter (fi-667PR)	PA03576-D101	Assists document management by printing numbers, Roman characters and codes on original documents after they have been scanned.

■ Consumables

Description	Parts number	Comments
Pick Roller	PA03338-K011	Lifetime: Every 250,000 sheets or one year These rollers feed documents into the scanner.
Brake Roller	PA03576-K010	Lifetime: Every 250,000 sheets or one year These rollers separate documents as they are being fed into the scanner.
Print Cartridge	C A00050-0262	Lifetime: 4,000,000 printed characters fi-667PR print head

■ Trademarks

* ISIS is a registered trademark of EMC Corporation in the United States.
* Microsoft, Windows, Windows Server and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
* Other company names and product names are the registered trademarks or trademarks of the respective companies.

OMR Solutions

H.O.: 503, DLF Prime Towers, Okhla Delhi
M.: +91 9319123429 +91 8954800532



PFU Limited, a Fujitsu company, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.

Visit the fi Series web site for ordering and purchasing information
<http://imagescanner.fujitsu.com/>